



AXON PRODUCTS

307 ECHELON ROAD • GREENVILLE, SC 29605
TEL. 864-299-2819 • FAX 864-299-2820
EMAIL info@axonproducts.com

AEROSPACE TECHNICAL DATA

AX-17 POLYURETHANE ACCELERATOR

Revised: April 2007

PRODUCT DESCRIPTION:

Polyurethane accelerators are intended to speed up the drying of polyurethane topcoats. Typical uses include repair and touch up, application of small areas such as stripes, numbers or other markings. In cooler conditions, between 45-65°F, AX-17 will be especially helpful.

SURFACE PREPARATION:

After mixing the paint well, the AX-17 accelerator should be added and stirred in thoroughly.

MIXING / APPLICATION:

Generally one-half ounce (approx. 15 ml) of AX-17 per mixed gallon of polyurethane topcoat is recommended. Pot life of the accelerated paint will be shorter, typically being reduced by 1/3 to 1/2 of normal usable times. Excessive amounts of AX-17 can cause reductions in the long-term durability of the polyurethane topcoat.

PHYSICAL PROPERTIES:

Appearance:	Clear, thin solution
Density:	8.14 lbs/gallon
Shelf Life:	1 year from date of manufacture

PRECAUTIONS:

Use with adequate ventilation and proper respiratory protection. See MSDS for complete instructions and precautions.